

Engineered for Professional Security



17"/19" TFT-LCD Monitor
SMT-1712/1912


Superior Image Quality

Producing 1,280x1,024 resolution, SMT-1712 and SMT-1912 feature 5ms response time, 5,000:1 Dynamic Contrast, (1,000:1 standard), 300cd/m² brightness and 160° view angle.



Protective Tempered Glass Screen

Monitor screen with super-clear protective tempered glass help to avoid accidental damage to the panel by users. SMT-1712/1912 is resistant to the dirt and repetitive touching/scratching. Also, the screen can be easily cleaned with non-abrasive soap and water.



60,000 Hours of MTTF

SMT-1712/1912 is optimized for 24/7 surveillance environment, featuring specialized design which provides 60,000 hours of MTTF (MeantimeTo Failure).



Environment-friendly Low Power Consumption

The lowest power consumption in operating mode saves energy and money, especially for 24/7 operating environments



Signal Balance for Long Distance Installation

The signal balance function eliminates the attenuation of RGB signal in the long signal cables, signal dividers, and graphic cards.



17"/19" TFT-LCD Monitor

SMT-1712/1912




Features

- Signal balance function for weak RGB signal
- Support up to 1,280 x 1,024 resolution
- Dynamic contrast 5,000:1
- Fast response time 5ms
- Durable tempered glass screen
- Simple desktop stand
- VESA mount compatible

Specifications

Model	SMT-1712	SMT-1912
General		
Screen Size	17"	19"
Resolution (HxV)	1,280 x 1,024	
Pixel Pitch (mm)	0.264 x 0.264(HxV)	0.294 x 0.294(HxV)
Brightness(cd/m ²)	300	
Contrast Ratio	1,000:1 (Dynamic Contrast Ratio 5,000:1)	
Response Time (ms)	5	
Viewing Angle (H/V)	160° / 160°	
Backlight Type	4 CCFT(2 Dual)	
Panel Lamp Life	50,000HR	
Display Colors	16.7M	
Horizontal Frequency	31 ~ 81KHz	
Vertical Frequency	56 ~ 75Hz	
Sync Format	NTSC : 3.5 / PAL : 4.43	
Feature		
Tempered Glass	Yes	
Language	English / French / German / Italian / Portuguese / Russian / Spanish / Swedish / Chinese / Japanese / Korean / Turkish / Taiwanese	
Front Panel Control	Menu, Adjust up / down / Auto / Enter, Power	
VESA Mount	100 x 100 mm	
Input Interface	PC	
Stand	Swivel Stand	
Power Requirement	AC100-240V, 50/60Hz	
Power Consumption	33W	36W
Weight	4.9Kg	5.45Kg
Dimensions	371(W) x 404(H) x 217(D)mm	412(W) x 422(H) x 217(D)mm
Accessories	Quick Set-up Guide, Power Cord, Video Signal Cable, CD-ROM	

Dimensions (unit:mm)



ELECTRONICS

SAMSUNG ELECTRONICS CO., LTD.

416, Maetan 3 Dong, YeongTong-Gu, Suwon City, Kyeonggi-Do, Korea, 443-742
Tel: +82-31-277-3342~3347 Fax: +82-31-277-6597 www.samsungsecurity.com

Distributed by

* Design and specifications are subject to change without notice